

## High speed grounding kit for CELLFLEX® LCF 12



### Product Description

This Grounding Kit has been developed by RFS for the CELLFLEX® cable series. The Grounding Kit body facilitates a proper attachment to the coaxial cable, ensuring that the performance of the coaxial cable is not being compromised. The tin plated copper mesh provides a secure, low resistance contact to the cable outer conductor. The installation only takes a few minutes. No additional sealing with mastic and electrical tape required.



### Features/Benefits

• Compatible with both copper and aluminium cable types i.e. one Grounding Kit for both outer conductor materials eliminates the risk of faulty

Grounding Kit installation and helps to keep inventory down.

• This kit has been verified by independent labs to withstand the damaging effects of lightning current in excess of 50kA 10/350µs according to

EN 50164. The copper wire provides the most practical and effective low inductance transfer of lightning induced current to ground.

• No influence on the electrical transmission characteristics of the coaxial cable.

• Robust mechanical design.

• UV resistant according to DIN EN ISO 4892-2 (Plastics – Methods of exposure to laboratory light sources – Part 2 Xenon-arc-lamps).

• Ozone resistant according to DIN 53509 (Testing of rubber – Determination of resistance to ozone cracking).

• Compliant to RoHS (EU 2002/95/EC) and CRoHS (China SJ/T11363-2006) i.e. usable on a global basis.

### Technical Specifications

Product Line	Coaxial Cable Accessories
Product Type	Grounding Kit
Type of Grounding Kit	High Speed
Transmission Line Type	LCF12
Coaxial Cable Type	Foam Dielectric
Cable Size	1/2"
Recommended Tool	JSTRIP-12-3
Lug Attachment Method	Factory Attached
Lug Style Size	1-hole Ø 10.2mm (13/32") crimp-on, tin-plated
Grounding Wire Length, m (in)	0.5 (19.5)
Grounding Wire Size	6 AWG (7 strand)
Grounding Wire Color	Black
Grounding Body Color	Black
Color	Black
Material	Grounding Kit Body: Stainless steel, with vulcanised EPDM (Ethylene-Propylene-Caoutchouc) Screws: Stainless steel with safety washers Contact element: Tin-plated copper mesh
Sealing Class	IP66 and IP68 (0.5 bar @ 1 hour)
Operation Temperature, °C(°F)	-50 to +85 (-58 to +185)
Storage Temperature, °C(°F)	-50 to +85 (-58 to +185)
Package Quantity	1
Weight per piece, kg (lb)	0.3 (0.66)

### Notes